



## TECHNICAL PARAMETERS

<b>Voltage</b>	AC 90–265 V	<b>LED chips</b>	SMD
<b>Frequency range</b>	50 ~ 60 Hz	<b>Protection class</b>	I.
<b>Working temperature</b>	-40 °C to +45 °C	<b>Material</b>	Aluminium
<b>Colour rendering index</b>	75 Ra	<b>Power factor</b>	min. 0,95
<b>IP rating</b>	IP 65	<b>IK rating</b>	IK09
<b>Lifetime</b>	100 000 h	<b>Color</b>	Anthracite
<b>Overvoltage protection</b>	min. 6kV	<b>Mounting</b>	Post-top

## PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	B (mm)	C (mm)	C (mm)
20198	16 W	4000K	2420 lm	standard	152 lm/W	Tempered glass	2,6 kg	600	90	115
20199	16 W	4000K	2420 lm	DIM	152 lm/W	Tempered glass	2,6 kg	600	90	115
20200	24 W	4000K	3290 lm	standard	137 lm/W	Tempered glass	2,6 kg	600	90	115
20201	24 W	4000K	3290 lm	DIM	137 lm/W	Tempered glass	2,6 kg	600	90	115
20202	33 W	4000K	4290 lm	standard	130 lm/W	Tempered glass	2,6 kg	600	90	115
20203	33 W	4000K	4290 lm	DIM	130 lm/W	Tempered glass	2,6 kg	600	90	115
20204	48 W	4000K	5450 lm	standard	114 lm/W	Tempered glass	2,6 kg	600	90	115
20205	48 W	4000K	5450 lm	DIM	114 lm/W	Tempered glass	2,6 kg	600	90	115
20206	16 W	2700K	2300 lm	standard	144 lm/W	Tempered glass	2,6 kg	600	90	115
20207	16 W	2700K	2300 lm	DIM	144 lm/W	Tempered glass	2,6 kg	600	90	115
20208	24 W	2700K	3130 lm	standard	131 lm/W	Tempered glass	2,6 kg	600	90	115
20209	24 W	2700K	3130 lm	DIM	131 lm/W	Tempered glass	2,6 kg	600	90	115
20210	33 W	2700K	4080 lm	standard	124 lm/W	Tempered glass	2,6 kg	600	90	115
20211	33 W	2700K	4080 lm	DIM	124 lm/W	Tempered glass	2,6 kg	600	90	115
20212	48 W	2700K	5170 lm	standard	108 lm/W	Tempered glass	2,6 kg	600	90	115
20213	48 W	2700K	5170 lm	DIM	108 lm/W	Tempered glass	2,6 kg	600	90	115