



## TECHNICAL PARAMETERS

Voltage	AC 100-277 V	LED chips	SMD
Frequency range	50 ~ 60 Hz	Protection class	I.
Working temperature	-40 °C to +55 °C	Material	Aluminium
Colour rendering index	80 Ra	Power factor	min. 0,95
IP rating	IP 54	IK rating	IK08
Lifetime	50 000 h	Color	Steel
Beam angle	120°	Mounting	Suspended

## PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	A (mm)	B (mm)	C (mm)
20124	45 W	4000 K	7570 lm	standard	168 lm/W	PMMA	3,1 kg	480	135	130
20125	45 W	4000 K	7570 lm	DALI	168 lm/W	PMMA	3,1 kg	480	135	130
20126	45 W	5000 K	7570 lm	standard	168 lm/W	PMMA	3,1 kg	480	135	130
20127	45 W	5000 K	7570 lm	DALI	168 lm/W	PMMA	3,1 kg	480	135	130
20128	69W	4000 K	10955 lm	standard	157 lm/W	PMMA	3,5 kg	580	135	130
20129	69W	4000 K	10955 lm	DALI	157 lm/W	PMMA	3,5 kg	580	135	130
20130	69W	5000 K	10955 lm	standard	157 lm/W	PMMA	3,5 kg	580	135	130
20131	69W	5000 K	10955 lm	DALI	157 lm/W	PMMA	3,5 kg	580	135	130
20132	90W	4000 K	15141 lm	standard	168 lm/W	PMMA	7,5 kg	1130	135	130
20133	90W	4000 K	15141 lm	DALI	168 lm/W	PMMA	7,5 kg	1130	135	130
20134	90W	5000 K	15141 lm	standard	168 lm/W	PMMA	7,5 kg	1130	135	130
20135	90W	5000 K	15141 lm	DALI	168 lm/W	PMMA	7,5 kg	1130	135	130
20136	135 W	4000 K	22711 lm	standard	168 lm/W	PMMA	9,5 kg	1680	135	130
20137	135 W	4000 K	22711 lm	DALI	168 lm/W	PMMA	9,5 kg	1680	135	130
20138	135 W	5000 K	22711 lm	standard	168 lm/W	PMMA	9,5 kg	1680	135	130
20139	135 W	5000 K	22711 lm	DALI	168 lm/W	PMMA	9,5 kg	1680	135	130
20140	139 W	4000 K	21918 lm	standard	158 lm/W	PMMA	7,5 kg	1130	135	130
20141	139 W	4000 K	21918 lm	DALI	158 lm/W	PMMA	7,5 kg	1130	135	130
20142	139 W	5000 K	21918 lm	standard	158 lm/W	PMMA	7,5 kg	1130	135	130
20143	139 W	5000 K	21918 lm	DALI	158 lm/W	PMMA	7,5 kg	1130	135	130

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	A (mm)	B (mm)	C (mm)
20144	208 W	4000 K	32873 lm	standard	158 lm/W	PMMA	9,5 kg	1680	135	130
20145	208 W	4000 K	32873 lm	DALI	158 lm/W	PMMA	9,5 kg	1680	135	130
20146	208 W	5000 K	32873 lm	standard	158 lm/W	PMMA	9,5 kg	1680	135	130
20147	208 W	5000 K	32873 lm	DALI	158 lm/W	PMMA	9,5 kg	1680	135	130
20148	130 W	4000 K	15141 lm	standard	109 lm/W	PMMA	4 kg	710	135	130
20149	130 W	4000 K	15141 lm	DALI	109 lm/W	PMMA	4 kg	710	135	130
20150	130 W	5000 K	15141 lm	standard	109 lm/W	PMMA	4 kg	710	135	130
20151	130 W	5000 K	15141 lm	DALI	109 lm/W	PMMA	4 kg	710	135	130