



TECHNICAL PARAMETERS

Voltage	AC 90-265 V	Diffuser	PC
Frequency range	50 ~ 60 Hz	LED chip	SMD
Working temperature	-35 °C to +35 °C	Protection class	I.
Colour rendering index	80 Ra	Material	metal
IP rating	IP 44	Color	white
Lifetime	50 000 h	Mounting	surface
Beam angle	115°	Energy class	G

PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	WEIGHT	A (mm)	C (mm)
133-0041	12 W	2700 K / 4000 K / 6500 K	825 lm	standard	70 lm/W	0,5 kg	Ø260	85
133-0077	18 W	2700 K / 4000 K / 6500 K	1210 lm	standard	70 lm/W	0,8 kg	Ø330	100
133-0024	24 W	2700 K / 4000 K / 6500 K	1680 lm	standard	70 lm/W	1,1 kg	Ø400	110
133-0026	36 W	2700 K / 4000 K / 6500 K	2520 lm	standard	70 lm/W	1,6 kg	Ø500	110
133-0044	72 W	2700 K / 4000 K / 6500 K	5040 lm	standard	70 lm/W	1,8 kg	Ø800	110