



TECHNICAL PARAMETERS

Voltage	AC 90-265 V	Color temperature	4000K
Frequency range	50 ~ 60 Hz	Diffuser	PMMA
Working temperature	-40 °C to +35 °C	LED chips	SMD
Colour rendering index	80 Ra	Protection class	I.
IP rating	IP 20	Material	wood
Lifetime	50 000 h	Driver	standard
Beam angle	120°	Mounting	surface

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	LUMINOUS FLUX	LUMINAIRE EFFICACY	COLOR	WEIGHT	ENERGY CLASS	A (mm)	B (mm)	C (mm)
135-0430	24 W	1430 lm	60 lm / W	Oak	1,4 kg	G	300	300	65
135-0410	40 W	3320 lm	80 lm / W	Oak	3,7 kg	F	600	600	65
20575	24 W	1430 lm	60 lm / W	Pine	1,4 kg	G	300	300	65
20576	40 W	3320 lm	80 lm / W	Pine	3,7 kg	F	600	600	65
21065	24 W	1430 lm	60 lm / W	Ash	1,4 kg	G	300	300	65
21066	40 W	3320 lm	80 lm / W	Ash	3,7 kg	F	600	600	65