



## TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PA
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	II.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 41	Color	white
Lifetime	50 000 h	Mounting	recessed
Beam angle	115°	Energy class	E / F
Weight	3 kg		

## PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20316	40 W	4000 K	3505 lm	standard		88 lm/W	595	595	35
20317	40 W	4000 K	3505 lm	DALI		88 lm/W	595	595	35
20318	40 W	4000 K	3505 lm	standard	1H	88 lm/W	595	595	35
20319	40 W	4000 K	3505 lm	standard	3H	88 lm/W	595	595	35
20320	40 W	4000 K	3505 lm	DALI	1H	88 lm/W	595	595	35
20321	40 W	4000 K	3505 lm	DALI	3H	88 lm/W	595	595	35
20418	29 W	4000 K	2813 lm	standard		97 lm/W	595	595	35
20419	29 W	4000 K	2813 lm	DALI		97 lm/W	595	595	35
20420	29 W	4000 K	2813 lm	standard	1H	97 lm/W	595	595	35
20421	29 W	4000 K	2813 lm	standard	3H	97 lm/W	595	595	35
20422	29 W	4000 K	2813 lm	DALI	1H	97 lm/W	595	595	35
20423	29 W	4000 K	2813 lm	DALI	3H	97 lm/W	595	595	35
20424	34 W	4000 K	3112 lm	standard		92 lm/W	595	595	35
20425	34 W	4000 K	3112 lm	DALI		92 lm/W	595	595	35
20426	34 W	4000 K	3112 lm	standard	1H	92 lm/W	595	595	35
20427	34 W	4000 K	3112 lm	standard	3H	92 lm/W	595	595	35
20428	34 W	4000 K	3112 lm	DALI	1H	92 lm/W	595	595	35
20429	34 W	4000 K	3112 lm	DALI	3H	92 lm/W	595	595	35

# QUADRA BACKLIT

LED interior lighting

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20430	38 W	4000 K	3383 lm	standard		89 lm/W	595	595	35
20431	38 W	4000 K	3383 lm	DALI		89 lm/W	595	595	35
20432	38 W	4000 K	3383 lm	standard	1H	89 lm/W	595	595	35
20433	38 W	4000 K	3383 lm	standard	3H	89 lm/W	595	595	35
20434	38 W	4000 K	3383 lm	DALI	1H	89 lm/W	595	595	35
20435	38 W	4000 K	3383 lm	DALI	3H	89 lm/W	595	595	35
20436	48 W	4000 K	4039 lm	standard		84 lm/W	595	595	35
20437	48 W	4000 K	4039 lm	DALI		84 lm/W	595	595	35
20438	48 W	4000 K	4039 lm	standard	1H	84 lm/W	595	595	35
20439	48 W	4000 K	4039 lm	standard	3H	84 lm/W	595	595	35
20440	48 W	4000 K	4039 lm	DALI	1H	84 lm/W	595	595	35
20441	48 W	4000 K	4039 lm	DALI	3H	84 lm/W	595	595	35
20442	55 W	4000 K	4399 lm	standard		80 lm/W	595	595	35
20443	55 W	4000 K	4399 lm	DALI		80 lm/W	595	595	35
20444	55 W	4000 K	4399 lm	standard	1H	80 lm/W	595	595	35
20445	55 W	4000 K	4399 lm	standard	3H	80 lm/W	595	595	35
20446	55 W	4000 K	4399 lm	DALI	1H	80 lm/W	595	595	35
20447	55 W	4000 K	4399 lm	DALI	3H	80 lm/W	595	595	35
20448	59 W	4000 K	4598 lm	standard		78 lm/W	595	595	35
20449	59 W	4000 K	4598 lm	DALI		78 lm/W	595	595	35
20450	59 W	4000 K	4598 lm	standard	1H	78 lm/W	595	595	35
20451	59 W	4000 K	4598 lm	standard	3H	78 lm/W	595	595	35
20452	59 W	4000 K	4598 lm	DALI	1H	78 lm/W	595	595	35
20453	59 W	4000 K	4598 lm	DALI	3H	78 lm/W	595	595	35