



TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PS
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	II.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 41	Color	white
Lifetime	50 000 h	Mounting	recessed
Beam angle	115°	Energy class	F
Weight	3,4 kg		

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20400	45 W	4000 K	3827 lm	standard		85 lm/W	1195	295	35
20401	45 W	4000 K	3827 lm	DALI		85 lm/W	1195	295	35
20402	45 W	4000 K	3827 lm	standard	1H	85 lm/W	1195	295	35
20403	45 W	4000 K	3827 lm	standard	3H	85 lm/W	1195	295	35
20404	45 W	4000 K	3827 lm	DALI	1H	85 lm/W	1195	295	35
20405	45 W	4000 K	3827 lm	DALI	3H	85 lm/W	1195	295	35