



## TECHNICAL PARAMETERS

Voltage	AC 90-265 V	Diffuser	PMMA/LGP
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	II.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 20	Color	white
Lifetime	50 000 h	Mounting	recessed
Beam angle	115°	Energy class	F
Weight	3,4 kg		

## PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20364	40 W	4000 K	3400 lm	standard		85 lm/W	1195	295	10
20365	40 W	4000 K	3400 lm	DALI		85 lm/W	1195	295	10
20366	40 W	4000 K	3400 lm	standard	1H	85 lm/W	1195	295	10
20367	40 W	4000 K	3400 lm	standard	3H	85 lm/W	1195	295	10
20368	40 W	4000 K	3400 lm	DALI	1H	85 lm/W	1195	295	10
20369	40 W	4000 K	3400 lm	DALI	3H	85 lm/W	1195	295	10
20370	36 W	4000 K	4320 lm	standard		120 lm/W	1195	295	10
20371	36 W	4000 K	4320 lm	DALI		120 lm/W	1195	295	10
20372	36 W	4000 K	4320 lm	standard	1H	120 lm/W	1195	295	10
20373	36 W	4000 K	4320 lm	standard	3H	120 lm/W	1195	295	10
20374	36 W	4000 K	4320 lm	DALI	1H	120 lm/W	1195	295	10
20375	36 W	4000 K	4320 lm	DALI	3H	120 lm/W	1195	295	10