



TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PA
Frequency range	50 ~ 60 Hz	LED chip	SMD
Working temperature	-40 °C to +35 °C	Protection class	I.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 20	Color	standard
Lifetime	50 000 h	Mounting	suspended
Beam angle	120°	Energy class	E

PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	COLOR	LUMINAIRE EFFICACY	WEIGHT	A (mm)	B (mm)	C (mm)
21084	58 W	3000 K	4350 lm	black	75 lm/W	3 kg	1500	50	70
21085	58 W	3000 K	4350 lm	white	75 lm/W	3 kg	1500	50	70
21086	58 W	3000 K	4350 lm	silver	75 lm/W	3 kg	1500	50	70
21087	46 W	3000 K	3387 lm	black	75 lm/W	2,5 kg	1200	50	70
21088	46 W	3000 K	3387 lm	white	75 lm/W	2,5 kg	1200	50	70
21089	46 W	3000 K	3387 lm	silver	75 lm/W	2,5 kg	1200	50	70
21090	23 W	3000 K	1820 lm	black	75 lm/W	1,5 kg	600	50	70
21091	23 W	3000 K	1820 lm	white	75 lm/W	1,5 kg	600	50	70
21092	23 W	3000 K	1820 lm	silver	75 lm/W	1,5 kg	600	50	70