



## TECHNICAL PARAMETERS

<b>Voltage</b>	AC 90-265 V	<b>LED chips</b>	SMD
<b>Frequency range</b>	50 ~ 60 Hz	<b>Protection class</b>	I.
<b>Working temperature</b>	-40 °C to +50 °C	<b>Material</b>	Die-cast aluminium
<b>Colour rendering index</b>	75 Ra	<b>Power factor</b>	min. 0,95
<b>IP rating</b>	IP65	<b>IK rating</b>	IK09
<b>Lifetime</b>	100 000 h	<b>Color</b>	Anthracite
<b>Overvoltage protection</b>	min. 6kV	<b>Mounting</b>	Post-top

## PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	B (mm)	C (mm)	C (mm)
20250	30W	4000K	3000 lm	standard	100 lm/W	PC	5kg	690	480	76
20251	30W	4000K	3000 lm	AstroDIM	100 lm/W	PC	5kg	690	480	76
20252	40W	4000K	4000 lm	standard	100 lm/W	PC	5kg	690	480	76
20253	40W	4000K	4000 lm	AstroDIM	100 lm/W	PC	5kg	690	480	76
20254	50W	4000K	5000 lm	standard	100 lm/W	PC	5kg	690	480	76
20255	50W	4000K	5000 lm	AstroDIM	100 lm/W	PC	5kg	690	480	76
20256	30W	2700K	2850 lm	standard	95 lm/W	PC	5kg	690	480	76
20257	30W	2700K	2850 lm	AstroDIM	95 lm/W	PC	5kg	690	480	76
20258	40W	2700K	3800 lm	standard	95 lm/W	PC	5kg	690	480	76
20259	40W	2700K	3800 lm	AstroDIM	95 lm/W	PC	5kg	690	480	76
20260	50W	2700K	4750 lm	standard	95 lm/W	PC	5kg	690	480	76
20261	50W	2700K	4750 lm	AstroDIM	95 lm/W	PC	5kg	690	480	76