



TECHNICAL PARAMETERS

Voltage	AC 90–265 V; AC 220 - 240 V	Diffuser	PMMA
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	I.; II.
Colour rendering index	80 Ra	Material	wood
IP rating	IP 20	Driver	standard
Lifetime	50 000 h	Mounting	surface
Beam angle	120°		

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	LUMINAIRE EFFICACY	COLOR	WEIGHT	ENERGY CLASS	A (mm)	C (mm)
21613	6 W	3000 K	531 lm	89 lm / W	Oak	0,6 kg	F	130	60
21615	6 W	4000 K	575 lm	96 lm / W	Oak	0,6 kg	E	130	60
21614	12 W	3000 K	1111 lm	93 lm / W	Oak	0,3 kg	F	200	60
21616	12 W	4000 K	1250 lm	104 lm / W	Oak	0,3 kg	E	200	60
134-0456	24 W	4000 K	1600 lm	60 lm / W	Oak	1,3 kg	G	300	60
134-0457	36 W	4000 K	2800 lm	60 lm / W	Oak	1,5 kg	F	400	60
134-0458	48 W	4000 K	3600 lm	60 lm / W	Oak	2,2 kg	F	500	60
20577	24 W	4000 K	1600 lm	60 lm / W	Pine	1,3 kg	G	300	60
20578	36 W	4000 K	2800 lm	60 lm / W	Pine	1,5 kg	F	400	60
20579	48 W	4000 K	3600 lm	60 lm / W	Pine	2,2 kg	F	500	60
21067	24 W	4000 K	1600 lm	60 lm / W	Ash	1,3 kg	G	300	60
21068	36 W	4000 K	2800 lm	60 lm / W	Ash	1,5 kg	F	400	60
21069	48 W	4000 K	3600 lm	60 lm / W	Ash	2,2 kg	F	500	60