



TECHNICAL PARAMETERS

Voltage	AC 100-277 V	LED chips	SMD
Frequency range	50 ~ 60 Hz	Protection class	I.
Working temperature	-40 °C to +65 °C	Material	Aluminium
Colour rendering index	80 Ra	Power factor	min. 0,95
IP rating	IP 65	IK rating	IK08
Lifetime	50 000 h	Color	Steel
Beam angle	120°	Mounting	Suspended

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	A (mm)	B (mm)	C (mm)
20083	90 W	4000 K	15140 lm	standard	168 lm/W	PMMA	7 kg	580	310	130
20084	90 W	4000 K	15140 lm	DALI	168 lm/W	PMMA	7 kg	580	310	130
20085	90 W	5000 K	15140 lm	standard	168 lm/W	PMMA	7 kg	580	310	130
20086	90 W	5000 K	15140 lm	DALI	168 lm/W	PMMA	7 kg	580	310	130
20087	278 W	4000 K	43836 lm	standard	158 lm/W	PMMA	15 kg	1130	310	130
20088	278 W	4000 K	43836 lm	DALI	158 lm/W	PMMA	15 kg	1130	310	130
20089	278 W	5000 K	43836 lm	standard	158 lm/W	PMMA	15 kg	1130	310	130
20119	278 W	5000 K	43836 lm	DALI	158 lm/W	PMMA	15 kg	1130	310	130
20120	260 W	4000 K	30282 lm	standard	116 lm/W	PMMA	9 kg	710	310	130
20121	260 W	4000 K	30282 lm	DALI	116 lm/W	PMMA	9 kg	710	310	130
20122	260 W	5000 K	30282 lm	standard	116 lm/W	PMMA	9 kg	710	310	130
20123	260 W	5000 K	30282 lm	DALI	116 lm/W	PMMA	9 kg	710	310	130