



TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PS
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	II.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 41	Color	white
Lifetime	50 000 h	Mounting	recessed
Beam angle	115°	Energy class	F
Weight	3 kg		

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20376	40 W	4000 K	3308 lm	standard		83 lm/W	595	595	35
20377	40 W	4000 K	3308 lm	DALI		83 lm/W	595	595	35
20378	40 W	4000 K	3308 lm	standard	1H	83 lm/W	595	595	35
20379	40 W	4000 K	3308 lm	standard	3H	83 lm/W	595	595	35
20380	40 W	4000 K	3308 lm	DALI	1H	83 lm/W	595	595	35
20381	40 W	4000 K	3308 lm	DALI	3H	83 lm/W	595	595	35
20382	35 W	4000 K	2992 lm	standard		85 lm/W	595	595	35
20383	35 W	4000 K	2992 lm	DALI		85 lm/W	595	595	35
20384	35 W	4000 K	2992 lm	standard	1H	85 lm/W	595	595	35
20385	35 W	4000 K	2992 lm	standard	3H	85 lm/W	595	595	35
20386	35 W	4000 K	2992 lm	DALI	1H	85 lm/W	595	595	35
20387	35 W	4000 K	2992 lm	DALI	3H	85 lm/W	595	595	35
20388	51 W	4000 K	3913 lm	standard		77 lm/W	595	595	35
20389	51 W	4000 K	3913 lm	DALI		77 lm/W	595	595	35
20390	51 W	4000 K	3913 lm	standard	1H	77 lm/W	595	595	35
20391	51 W	4000 K	3913 lm	standard	3H	77 lm/W	595	595	35
20392	51 W	4000 K	3913 lm	DALI	1H	77 lm/W	595	595	35
20393	51 W	4000 K	3913 lm	DALI	3H	77 lm/W	595	595	35

QUADRA BACKLIT UGR

LED interior lighting

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20394	55 W	4000 K	4129 lm	standard		75 lm/W	595	595	35
20395	55 W	4000 K	4129 lm	DALI		75 lm/W	595	595	35
20396	55 W	4000 K	4129 lm	standard	1H	75 lm/W	595	595	35
20397	55 W	4000 K	4129 lm	standard	3H	75 lm/W	595	595	35
20398	55 W	4000 K	4129 lm	DALI	1H	75 lm/W	595	595	35
20399	55 W	4000 K	4129 lm	DALI	3H	75 lm/W	595	595	35