



TECHNICAL PARAMETERS

Voltage	AC 90-265 V	LED chips	SMD
Frequency range	50 ~ 60 Hz	Protection class	I.
Working temperature	-40 °C to +45 °C	Material	Aluminium
Colour rendering index	75 Ra	Power factor	min. 0,95
IP rating	IP 65	IK rating	IK09
Lifetime	100 000 h	Color	Anthracite
Overvoltage protection	min. 6kV	Mounting	Post-top

PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	B (mm)	C (mm)	C (mm)
20274	72 W	4000K	10440 lm	standard	145 lm/W	PMMA	5,2 kg	600	186	50
20275	72 W	4000K	10440 lm	AstroDIM	145 lm/W	PMMA	5,2 kg	600	186	50
20276	90 W	4000K	12870 lm	standard	143 lm/W	PMMA	5,2 kg	600	186	50
20277	90 W	4000K	12870 lm	AstroDIM	143 lm/W	PMMA	5,2 kg	600	186	50
20278	116 W	4000K	16240 lm	standard	140 lm/W	PMMA	5,2 kg	600	186	50
20279	116 W	4000K	16240 lm	AstroDIM	140 lm/W	PMMA	5,2 kg	600	186	50
20280	72 W	2700K	9920 lm	standard	138 lm/W	PMMA	5,2 kg	600	186	50
20281	72 W	2700K	9920 lm	AstroDIM	138 lm/W	PMMA	5,2 kg	600	186	50
20282	90 W	2700K	12220 lm	standard	136 lm/W	PMMA	5,2 kg	600	186	50
20283	90 W	2700K	12220 lm	AstroDIM	136 lm/W	PMMA	5,2 kg	600	186	50
20284	116 W	2700K	15430 lm	standard	132 lm/W	PMMA	5,2 kg	600	186	50
20285	116 W	2700K	15430 lm	AstroDIM	132 lm/W	PMMA	5,2 kg	600	186	50