



## TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PA
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	I.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 41	Weight	3 kg
Lifetime	50 000 h	Mounting	surface
Beam angle	115°	Energy class	F

## PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	COLOR	A (mm)	B (mm)	C (mm)
20328	40 W	4000 K	3512 lm	On/Off		88 lm/W	white	600	600	52
20329	40 W	4000 K	3512 lm	DALI		88 lm/W	white	600	600	52
20330	40 W	4000 K	3512 lm	On/Off	1H	88 lm/W	white	600	600	52
20331	40 W	4000 K	3512 lm	On/Off	3H	88 lm/W	white	600	600	52
20332	40 W	4000 K	3512 lm	DALI	1H	88 lm/W	white	600	600	52
20333	40 W	4000 K	3512 lm	DALI	3H	88 lm/W	white	600	600	52
21447	29 W	4000 K	2813 lm	On/Off		97 lm/W	black	600	600	52
21448	34 W	4000 K	3112 lm	On/Off		92 lm/W	black	600	600	52
21449	38 W	4000 K	3383 lm	On/Off		89 lm/W	black	600	600	52
21442	40 W	4000 K	3505 lm	On/Off		88 lm/W	black	600	600	52
21450	48 W	4000 K	4039 lm	On/Off		84 lm/W	black	600	600	52
21451	55 W	4000 K	4399 lm	On/Off		80 lm/W	black	600	600	52
21452	59 W	4000 K	4598 lm	On/Off		98 lm/W	black	600	600	52