



TECHNICAL PARAMETERS

Voltage	AC 90–265 V	Diffuser	PMMA/LGP
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	II.
Colour rendering index	80 Ra	Material	Aluminium
IP rating	IP 20	Color	white
Lifetime	50 000 h	Mounting	recessed
Beam angle	115°	Energy class	D / F
Weight	2,8 kg		

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	EMERGENCY DURATION	LUMINAIRE EFFICACY	A (mm)	B (mm)	C (mm)
20340	40 W	4000 K	3400 lm	standard		85 lm/W	595	595	10
20341	40 W	4000 K	3400 lm	DALI		85 lm/W	595	595	10
20342	40 W	4000 K	3400 lm	standard	1H	85 lm/W	595	595	10
20343	40 W	4000 K	3400 lm	standard	3H	85 lm/W	595	595	10
20344	40 W	4000 K	3400 lm	DALI	1H	85 lm/W	595	595	10
20345	40 W	4000 K	3400 lm	DALI	3H	85 lm/W	595	595	10
20346	36 W	4000 K	4320 lm	standard		120 lm/W	595	595	10
20347	36 W	4000 K	4320 lm	DALI		120 lm/W	595	595	10
20348	36 W	4000 K	4320 lm	standard	1H	120 lm/W	595	595	10
20349	36 W	4000 K	4320 lm	standard	3H	120 lm/W	595	595	10
20350	36 W	4000 K	4320 lm	DALI	1H	120 lm/W	595	595	10
20351	36 W	4000 K	4320 lm	DALI	3H	120 lm/W	595	595	10