



TECHNICAL PARAMETERS

Voltage	AC 90-305 V	LED chips	COB-chip
Frequency range	50 ~ 60 Hz	Protection class	I.
Working temperature	-30°C to +50°C	Material	Die-cast aluminium
Colour rendering index	80 Ra	Power factor	min. 0,95
IP rating	IP 65	IK rating	IK08
Lifetime	50 000 h	Color	black
Dimensions of the diffuser	Ø423 x h460	Mounting	suspended
Weight	6,5 kg	Energy class	E

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	BEAM ANGLE	DIFFUZER	Ø A (mm)	B (mm)
20102	30 W	4000 K	3000 lm	standard	100lm/W	60°	PC/Al	192	166
20103	30 W	4000 K	3000 lm	1-10V	100lm/W	90°	PC/Al	192	166
20104	30 W	4000 K	3000 lm	DALI	100lm/W	120°	PC/Al	192	166
20105	50 W	4000 K	5000 lm	standard	100lm/W	60°	PC/Al	192	166
20106	50 W	4000 K	5000 lm	1-10V	100lm/W	90°	PC/Al	192	166
20107	50 W	4000 K	5000 lm	DALI	100lm/W	120°	PC/Al	192	166
20108	100 W	4000 K	10000 lm	standard	100lm/W	60°	PC/Al	192	166
20109	100 W	4000 K	10000 lm	1-10V	100lm/W	90°	PC/Al	192	166
20110	100 W	4000 K	10000 lm	DALI	100lm/W	120°	PC/Al	192	166
20111	120 W	4000 K	12000 lm	standard	100lm/W	60°	PC/Al	192	166
20112	120 W	4000 K	12000 lm	1-10V	100lm/W	90°	PC/Al	192	166
20113	120 W	4000 K	12000 lm	DALI	100lm/W	120°	PC/Al	192	166
20114	200 W	4000 K	20000 lm	standard	100lm/W	60°	PC/Al	192	166
20115	200 W	4000 K	20000 lm	1-10V	100lm/W	90°	PC/Al	192	166
20116	200 W	4000 K	20000 lm	DALI	100lm/W	120°	PC/Al	192	166