



TECHNICAL PARAMETERS

Voltage	AC 90-265 V	Diffuser	PMMA
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C až +35 °C	Protection class	I.
Colour rendering index	80 Ra	Material	wood
IP rating	IP 20	Driver	standard
Lifetime	50 000 h	Mounting	suspended
Beam angle	120°	Energy class	F

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	LUMINAIRE EFFICACY	COLOR	WEIGHT	A (mm)	B (mm)	C (mm)
136-0620	36 W	4000 K	3000 lm	80 lm / W	Oak	4,4 kg	1200	82	85
136-0630	48 W	4000 K	3800 lm	80 lm / W	Oak	5,4 kg	1500	82	85
20573	36 W	4000 K	3000 lm	80 lm / W	Pine	4,4 kg	1200	82	85
20574	48 W	4000 K	3800 lm	80 lm / W	Pine	5,4 kg	1500	82	85
21063	36 W	4000 K	3000 lm	80 lm / W	Ash	4,4 kg	1200	82	85
21064	48 W	4000 K	3800 lm	80 lm / W	Ash	5,4 kg	1500	82	85