



TECHNICAL PARAMETERS

Voltage	AC 90–265 V	LED chips	SMD
Frequency range	50 ~ 60 Hz	Protection class	I.
Working temperature	-40 °C to +45 °C	Material	Aluminium
Colour rendering index	75 Ra	Power factor	min. 0,95
IP rating	IP 65	IK rating	IK09
Lifetime	100 000 h	Color	Anthracite
Overvoltage protection	min. 6kV	Mounting	Post-top

PRODUCT VARIANTS

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	WEIGHT	B (mm)	C (mm)	C (mm)
20286	12 W	2700 K	1740 lm	standard	145 lm/W	PMMA	3,5 kg	600	145	50
20287	12 W	2700 K	1740 lm	DALI	145 lm/W	PMMA	3,5 kg	600	145	50
20288	12 W	2700 K	1740 lm	AstroDIM	145 lm/W	PMMA	3,5 kg	600	145	50
20289	12 W	2700 K	1740 lm	AstroDIM+CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20290	12 W	2700 K	1740 lm	CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20291	19 W	2700 K	2755 lm	standard	145 lm/W	PMMA	3,5 kg	600	145	50
20292	19 W	2700 K	2755 lm	DALI	145 lm/W	PMMA	3,5 kg	600	145	50
20293	19 W	2700 K	2755 lm	AstroDIM	145 lm/W	PMMA	3,5 kg	600	145	50
20294	19 W	2700 K	2755 lm	AstroDIM+CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20295	19 W	2700 K	2755 lm	CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20296	25 W	2700 K	3625 lm	standard	145 lm/W	PMMA	3,5 kg	600	145	50
20297	25 W	2700 K	3625 lm	DALI	145 lm/W	PMMA	3,5 kg	600	145	50
20298	25 W	2700 K	3625 lm	AstroDIM	145 lm/W	PMMA	3,5 kg	600	145	50
20299	25 W	2700 K	3625 lm	AstroDIM+CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20300	25 W	2700 K	3625 lm	CLO	145 lm/W	PMMA	3,5 kg	600	145	50
20301	35 W	2700 K	5005 lm	standard	143 lm/W	PMMA	3,5 kg	600	145	50

ORDER NUMBER	POWER	COLOR TEMPERATURE	LUMINOUS FLUX	DRIVER	LUMINAIRE EFFICACY	DIFFUSER	A (mm)	B (mm)	C (mm)	C (mm)
20302	35 W	2700 K	5005 lm	DALI	143 lm/W	PMMA	3,5 kg	600	145	50
20303	35 W	2700 K	5005 lm	AstroDIM	143 lm/W	PMMA	3,5 kg	600	145	50
20304	35 W	2700 K	5005 lm	AstroDIM+CLO	143 lm/W	PMMA	3,5 kg	600	145	50
20305	35 W	2700 K	5005 lm	CLO	143 lm/W	PMMA	3,5 kg	600	145	50
20306	47 W	2700 K	6390 lm	standard	142 lm/W	PMMA	3,5 kg	600	145	50
20307	47 W	2700 K	6390 lm	DALI	142 lm/W	PMMA	3,5 kg	600	145	50
20308	47 W	2700 K	6390 lm	AstroDIM	142 lm/W	PMMA	3,5 kg	600	145	50
20309	47 W	2700 K	6390 lm	AstroDIM+CLO	142 lm/W	PMMA	3,5 kg	600	145	50
20310	47 W	2700 K	6390 lm	CLO	142 lm/W	PMMA	3,5 kg	600	145	50
20311	55 W	2700 K	7700 lm	standard	140 lm/W	PMMA	3,5 kg	600	145	50
20312	55 W	2700 K	7700 lm	DALI	140 lm/W	PMMA	3,5 kg	600	145	50
20313	55 W	2700 K	7700 lm	AstroDIM	140 lm/W	PMMA	3,5 kg	600	145	50
20314	55 W	2700 K	7700 lm	AstroDIM+CLO	140 lm/W	PMMA	3,5 kg	600	145	50
20315	55 W	2700 K	7700 lm	CLO	140 lm/W	PMMA	3,5 kg	600	145	50