



TECHNICAL PARAMETERS

Voltage	AC 90-265 V	Diffuser	PMMA
Frequency range	50 ~ 60 Hz	LED chips	SMD
Working temperature	-40 °C to +35 °C	Protection class	I.
Colour rendering index	80 Ra	Material	wood
IP rating	IP 20	Driver	standard
Lifetime	50 000 h	Mounting	surface
Beam angle	120°	Energy class	F

PRODUCT VARIANTS

ORDER NUMBER	WATTAGE	COLOR TEMPERATURE	LUMINOUS FLUX	LUMINAIRE EFFICACY	COLOR	WEIGHT	A (mm)	B (mm)	C (mm)
135-0420	42 W	4000K	3950 lm	90 lm / W	Oak	4,2 KG	1200	300	65
135-0421	42 W	3000K	3950 lm	90 lm / W	Oak	4,2 KG	1200	300	65
20571	42 W	4000K	3950 lm	90 lm / W	Pine	4,2 KG	1200	300	65
20572	42 W	3000K	3950 lm	90 lm / W	Pine	4,2 KG	1200	300	65
21061	42 W	4000K	3950 lm	90 lm / W	Ash	4,2 KG	1200	300	65
21062	42 W	3000K	3950 lm	90 lm / W	Ash	4,2 KG	1200	300	65